

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Magirus 503792271 Color Spray Light Grey 400 ml

Revision date: 08.10.2020

Product code: 94280

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Magirus 503792271 Color Spray Light Grey 400 ml

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Paints and varnishes

1.3. Details of the supplier of the safety data sheet

Company name:	Magirus GmbH	
Street:	Graf-Arco-Straße 30	
Place:	D-89079 Ulm	
Telephone:	+49 731 408 - 0	Telefax: +49 731 408 - 2410
e-mail:	magirus@cnhind.com	
Internet:	www.magirusgroup.com	

1.4. Emergency telephone

Vergiftungs-Informationen-Zentrale Freiburg

number:

+49 761-19 240

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Aerosol: Aerosol 1

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes serious eye irritation.

May cause drowsiness or dizziness.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

acetone

propan-2-ol

Signal word:

Danger

Pictograms:**Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Magirus 503792271 Color Spray Light Grey 400 ml

Revision date: 08.10.2020

Product code: 94280

Page 2 of 10

P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Chemical characterization

Paints and varnishes

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
67-64-1	acetone			25 - 50 %
	200-662-2	606-001-00-8		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
115-10-6	dimethyl ether			10 - 25 %
	204-065-8	603-019-00-8		
	Flam. Gas 1; H220			
108-65-6	2-methoxy-1-methylethyl acetate			2,5 - 10 %
	203-603-9	607-195-00-7		
	Flam. Liq. 3; H226			
67-63-0	propan-2-ol			2,5 - 10 %
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
1330-20-7	xylene			2,5 - 10 %
	215-535-7	601-022-00-9		
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304			
7397-62-8	Butyl glycolate			<1 %
	230-991-7			
	Repr. 2, Eye Dam. 1; H361 H318			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Provide fresh air. Put victim at rest, cover with a blanket and keep warm. If unconscious place in recovery position and seek medical advice.

After contact with skin

Wash with plenty of water. Change contaminated clothing. In case of skin irritation, consult a physician.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Magirus 503792271 Color Spray Light Grey 400 ml

Revision date: 08.10.2020

Product code: 94280

Page 3 of 10

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Vapours may cause drowsiness and dizziness. Frequently or prolonged contact with skin may cause dermal irritation.

The following symptoms may occur: Headache. Drowsiness. Dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂), Dry extinguishing powder, Foam.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protective suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Use only in well-ventilated areas. Keep away from sources of ignition - No smoking. Flammable vapours can accumulate in head space of closed systems. Caution! Transport usually takes place at temperatures above the flash point.

Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Magirus 503792271 Color Spray Light Grey 400 ml

Revision date: 08.10.2020

Product code: 94280

Page 4 of 10

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Hints on joint storage

Do not store together with: Material, oxygen-rich, oxidizing. Pyrophoric or self-heating substances.

Further information on storage conditions

Keep away from heat.

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
108-65-6	1-Methoxypropyl acetate	50	274		TWA (8 h)	WEL
		100	548		STEL (15 min)	WEL
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
115-10-6	Dimethyl ether	400	766		TWA (8 h)	WEL
		500	958		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

8.2. Exposure controls
Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. After work, wash hands and face. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles

Hand protection

Tested protective gloves must be worn.
 Suitable material: NBR (Nitrile rubber).
 Thickness of the glove material > 0,4mm
 penetration time (maximum wearing period): > 30 min.
 EN ISO 374

Skin protection

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. Avoid contact with skin, eyes and clothes.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Magirus 503792271 Color Spray Light Grey 400 ml

Revision date: 08.10.2020

Product code: 94280

Page 5 of 10

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection. Filtering device with filter or ventilator filtering device of type: AP2 (EN 140/143).

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Aerosol
Colour:	light grey
Odour:	characteristic
pH-Value:	not applicable
Changes in the physical state	
Melting point:	not determined
Initial boiling point and boiling range:	not determined
Flash point:	< -20 °C
Lower explosion limits:	1,2 vol. %
Upper explosion limits:	32,0 vol. %
Ignition temperature:	235 °C
Vapour pressure: (at 20 °C)	3,37 hPa
Density:	0,92 g/cm ³
Water solubility:	practically insoluble
Solvent content:	650 g/l

9.2. Other information

none

SECTION 10: Stability and reactivity**10.1. Reactivity**

Special hazards arising from the substance or mixture. There are no data available on the mixture itself.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

Pressurised container: May burst if heated. This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment).

10.5. Incompatible materials

Reacts with : Acid. alkali. Oxidizing agents.

10.6. Hazardous decomposition products

none

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Toxicokinetics, metabolism and distribution**

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Magirus 503792271 Color Spray Light Grey 400 ml

Revision date: 08.10.2020

Product code: 94280

Page 6 of 10

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-64-1	acetone				
	oral	LD50 mg/kg 5800	Rat	RTECS	
	dermal	LD50 mg/kg 20000	Rabbit	IUCLID	
	inhalation (4 h) vapour	LC50 76 mg/l	Rat		
108-65-6	2-methoxy-1-methylethyl acetate				
	oral	LD50 mg/kg 8532	Rat	RTECS	
	dermal	LD50 mg/kg 7500	Rabbit		
1330-20-7	xylene				
	dermal	ATE mg/kg 1100			
	inhalation vapour	ATE 11 mg/l			
	inhalation aerosol	ATE 1,5 mg/l			

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (acetone)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available

Additional information on tests

No data available

Practical experience
Observations relevant to classification

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 12: Ecological information
12.1. Toxicity

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Magirus 503792271 Color Spray Light Grey 400 ml

Revision date: 08.10.2020

Product code: 94280

Page 7 of 10

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-64-1	acetone					
	Acute fish toxicity	LC50 mg/l	5540	96 h	Onchorhynchus mykiss	
	Acute crustacea toxicity	EC50 mg/l	6100	48 h	Daphnia magna	
108-65-6	2-methoxy-1-methylethyl acetate					
	Acute fish toxicity	LC50	161 mg/l	96 h	Pimephales promelas	
	Acute crustacea toxicity	EC50	408 mg/l	48 h	Daphnia magna	

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone	-0,24
108-65-6	2-methoxy-1-methylethyl acetate	0,43

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

No data available

Further information

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Magirus 503792271 Color Spray Light Grey 400 ml

Revision date: 08.10.2020

Product code: 94280

Page 8 of 10

SECTION 14: Transport information
Land transport (ADR/RID)

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Transport category: 2
 Tunnel restriction code: D

Other applicable information (land transport)

E0

Inland waterways transport (ADN)

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L

Other applicable information (inland waterways transport)

E0

Marine transport (IMDG)

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2, see SP63

Special Provisions: 63, 190, 277, 327, 344, 959
 Limited quantity: See SP277
 EmS: F-D, S-U

Other applicable information (marine transport)

E0

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS, flammable

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Magirus 503792271 Color Spray Light Grey 400 ml

Revision date: 08.10.2020

Product code: 94280

Page 9 of 10

14.3. Transport hazard class(es):

2.1

Hazard label:

2.1



Special Provisions:

A145 A167 A802

Limited quantity Passenger:

30 kg G

IATA-packing instructions - Passenger:

203

IATA-max. quantity - Passenger:

75 kg

IATA-packing instructions - Cargo:

203

IATA-max. quantity - Cargo:

150 kg

Other applicable information (air transport)

E0

Passenger-LQ: Y203

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS:

yes


SECTION 15: Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3: acetone; 2-methoxy-1-methylethyl acetate

2010/75/EU (VOC): 650 g/l

2004/42/EC (VOC): 650 g/l

Subcategory according to Directive 2004/42/EC: Special finishes - All types, VOC limit value: 840 g/l

National regulatory information

Employment restrictions:

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe employment restrictions for women of child-bearing age.

Water hazard class (D):

2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information
Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Magirus 503792271 Color Spray Light Grey 400 ml

Revision date: 08.10.2020

Product code: 94280

Page 10 of 10

H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Coatings and paints, thinners, paint removers	-	-	9a	7, 11	11a	7, 7a	91	

LCS: Life cycle stages

SU: Sectors of use

PC: Product categories

PROC: Process categories

ERC: Environmental release categories

AC: Article categories

TF: Technical functions

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)